

Thank you for choosing DrawndPaint touch up paint DIY KIT. Our simple 3-step process allows anyone professionally apply the KIT to avoid high repair costs from typical body shops. So the value of your vehicle is increased. We strongly recommend you to go through the following application steps to obtain the best performance. Please note that our paint is not the typical touch-up paint you can source at the local dealerships or auto part shops. It is a special blend of selected paints and organic chemicals to ensure quick drying, easy removing of excess paint for the perfect results on damaged surfaces. Our technology is unique to bring eco-friendly detailing solutions for perfect factory match and superior quality. We formulate our colors and chemicals in the latest technology mixing process to guarantee color accuracy and original factory quality.

German-Patented Special Solutioned Cleaning Cloth Application Insurance

Unless your vehicle is very new, there is a small possibility that the color won't match exactly as the paint on the new models does not fade as quickly or badly as old paints did. Do not hesitate to apply the paint on the application surface until you have the desired tone and tint. Our patented chemical solutioned cloth ensures complete removal of the touch up at any time during the application safely. Special Solutioned Cleaning Cloth is your insurance for application mistakes.

In order to assist you faster please address all product and related questions to **support@drawndpaint.com**

With Our Best Regards, DrawndPaint Support Team
E-mail : **support@drawndpaint.com**
Web : **https://www.drawndpaint.com**



Application Steps

- Important note: If your order has have two different paint bottles in the kit, you have to repeat below application steps for each color separately.

1. Ensure that application surface to be repaired has been cleaned entirely by our patented cleaning solutioned cloth (Step2 - Clear) Make sure all dirt, wax and polish are removed and surface is ready for the touch up paint.

2. Apply the custom made paint by microbrush on the application area by thin layers, if necessary smear the paint flat across the chipped area with your finger or thumb whilst wearing the protective glove. Make sure the paint is smeared out flat. Than leave it for drying. Drying time of the paint anywhere between 40 seconds up to 5 minutes depending on the temperature and applied paint quantity.

3. Make a light pressure and run the towel across the surface to remove excess paint from the surface. Do not push the surface by towel so hard, let the blending solution do work. Repeat the step 3 until all the excess paint is removed from around the chip/scratch. Then leave it for dry for few minutes again.

Cosmetic Finishes

Waxing and polishing steps are cosmetic finishing's, not a must requirement for touch up applications. You can use them at your convenience parts of your car.

1. Natural and smooth Paste does not contain abrasives and additives. It is a fresh treatment for perfect color transition. Apply the paste on towel and rub the surface gently to mature touch up paint on the application surface.

2. Apply small quantity of finishing Wax to the microfiber cloth and smoothly rub over the entire application area. It is recommended that you wax the whole panel for the best visual results.

Tips

- Kit contents are placed below and on the separator in the box.
- Before the application shake the paint bottle well to avoid paint blobs.
- If you have re-painted parts on your vehicle, please make sure that paint is hardened / fixed enough before using the product. Generally, one month curing time is okay to use touch up paint on re-painted parts.
- Do not wash your vehicle with pressurized water minimum 1 week after the touch up application.
- For perfect results on deep chip marks, we recommend to repeat the application several times.
- You can use the paste in order to boost exceeds paint removal step If the solution performance is not satisfactory.